

FS-6025MFP

A3 MONOCHROME MULTIFUNCTIONAL

► print ► copy ► scan ► fax

IMPRESSIVE FEATURES AT AN INSPIRING PRICE

Your small team may not produce huge volumes of documents but it still needs a highly capable multifunctional at a flattering price. The FS-6025MFP delivers. Its core ability to print, copy and scan double-sided documents are enhanced by optional finishing, a superbly simple wizard-driven touch-screen control panel and environmentally-aware features such as 1W sleep mode.

- Up to 25 A4 pages per minute
- Time to first print: 8.0 seconds or less
- Double-sided print, copy, and colour scan as standard
- Optional network fax functionality
- Paper capacity up to 1,600 sheets and a range of paper-handling options
- Wizard or menu-based customisable control system
- Easy to install and operate
- Low noise emissions match desktop printers
- Long-life components provide unprecedented efficiency and reliability
- Exceptionally low printing costs in its class



The 50-sheet reversing document processor conveniently copies and scans both sides of the page in a single process.

Customisable colour touch-screen offers fast, personalised access to frequently-used functions.



FS-6025MFP

MONOCHROME MULTIFUNCTIONAL FOR A4/A3 FORMAT

ECOSYS™ With their long-life components, ECOSYS devices are designed to maximise durability and minimise both direct costs such as consumables, and indirect costs such as maintenance and administration. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add productivity-enhancing options and a wide-variety of paper-handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

PRESCRIBE II

With the Kyocera page design and control language PRESCRIBE IIc, even complex graphics, logos and forms (including multipart forms) can be created on any system and stored in the printer. They can be recalled from the printer's memory as needed, reducing network congestion.

The KM NetViewer

KMNet Viewer enables complete monitoring and control of all ECOSYS printers and Kyocera multifunction copiers from any Windows® PC. It provides ideal network administration using the industry-standard SNMP protocol.

Status Monitor and Command Center

The Status Monitor visually portrays the printer's condition and gives direct access to the Command Center for the modification of advanced settings not available in the standard driver (e.g. IP settings, sleep mode or disabling the control panel).

USB Host Interface for USB Flash Memory

PDF, XPS, TIFF or JPEG files can be printed directly from a USB Flash Memory device (e.g. USB stick) via the USB host interface. Documents are selected directly using the printer's control panel. No computer is required.

General

Technology: KYOCERA ECOSYS, Mono Laser

Engine speed: Up to 25/12 pages per minute A4/A3

Resolution: 600 x 600 dpi (print), 600 x 600 dpi (scan/copy)

Duty cycle: Max. 80,000 pages per month

Recommended monthly printing volume: Up to 4,000 pages**

Warm-up time: Approx. 20 seconds or less

Time to first print: Approx. 8 seconds or less

Time to first copy: Approx. 9.2 seconds or less (DP), 7.8 seconds or less (Platen Cover)

CPU: PowerPC 464 / 800 MHz

Memory: Standard 512 MB, max. 1,536 MB

Integrated accounting: 100 department codes

Dimensions with platen cover (WxDxH): 590 x 590 x 586.5 mm

Dimensions with Document Processor (WxDxH): 590 x 590 x 694 mm

Weight with platen cover: Approx. 46.5 kg including toner container

Weight with Document Processor: Approx. 52.2 kg including toner container

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption

Printing: 553 Watt

Copying: 553 Watt

Stand-by: 119 Watt

Sleep-mode: 1.0 Watt

Noise (ISO 7779/ISO 9296)

Printing: 59.8 dB(A)

Standby: 44.0 dB(A)

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 100-sheet multi-purpose tray, 45–256 gsm. 52–163 gsm (larger than A4/Letter size), A3, A4, A5, A6, B5, Letter, Legal, Folio, envelopes, Custom (98 x 148 to 297 x 432 mm)

500-sheet universal paper cassette, 60–163 gsm, A3, A4, A5, B5, Letter, Legal, Folio, max. input capacity with options: 1,600 sheets

Duplex unit: Duplex as standard supports 60–163 gsm

Reversing document processor: 50-sheet, Simplex scan 45–160 gsm. Duplex scan 50–120 gsm, A3, A4, A5, B5, Letter, Legal, Custom (140 x 182 to 297 x 432 mm)

Output capacity: Max. 300 sheets; 250 sheets face-down (Main Tray), 50 sheets (Job Separator Tray)

Your KYOCERA Business Partner:

Print functions

Controller language: PRESCRIBE

Emulations: PCL 6 (5e/XL), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print

Interface: USB 2.0 (High-Speed), USB Host 2.0, Fast Ethernet 10/100/1,000Base-TX, Slot for optional print server, Slot for optional Memory Card

Operating systems: All current Windows operating systems, MAC OS X Version 10.2 or higher, Unix, Linux as well as other operating systems on request

Fonts/bar codes: 93 outline fonts (PCL 6, KPDL3) + 8 (Windows Vista), OCR: OCR-A, OCR-A kana, OCR-B, OCR-B kana, OCR-kana bitmap fonts, 45 types of one-dimensional bar codes, 1 type of two-dimensional bar code (PDF 417)

Features: encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3

Copy functions

Max. original size: A3/Ledger

Continuous copying: 1–999

Zoom range: 25–400% in 1% steps

Preset magnification ratios: 5 Reductions/5 Enlargements

Features: Scan-once-copy-many, sort, 2in1, 4in1, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is required), copy density control, Prevent Bleed-Through

Exposure mode: Auto, manual: 7 steps

Image adjustments: Text, Photo, Text + Photo, Graphic/Map, Copy/Printout

Scan functions

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-PC, Scan to USB Host, TWAIN, WSD scan

Interface: Fast Ethernet 10/100Base-TX, USB Host 2.0

Scan speed: 40 ipm (300 dpi, A4, b/w), 20 ipm (300 dpi, A4 colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales per colour)

Max. scan size: A3, Ledger

Original recognition: Text, photo, text + photo, OCR

File types: TIFF, PDF, JPEG and XPS

Compression method: MMR /JPEG

Features: Integrated address book, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once

Fax functions (optional)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission speed: Less than 3 sec

Scanning speed: 2.0 seconds (Quick Scanning, Bitmap)

Address book: 200 entries

Interface: Fast Ethernet 10/100/1000Base-TX, Telephone interface

Scanning density

Normal: 8 dot/mm x 3.85 line/mm

Fine: 8 dot/mm x 7.7 line/mm

Superfine: 8 dot/mm x 15.4 line/mm

Ultrafine: 16 dot/mm x 15.4 line/mm

Halftone: 8 dot/mm x 7.7 line/mm

Maximum original size: A3, Ledger

Compression method: JBIG, MMR, MR, MH

Memory reception: 700 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

Options

Paper handling

PF-470 Paper feeder: Max. 500 sheets; 60–163 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)

PF-471 Paper feeder: Max. 1,000 sheets; 60–163 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)

DF-470 Document finisher: Max. 500 sheets 52–256 gsm; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm); 3 position stapling up to 50 sheets A4 or 25 sheets A3

AK-470 Attachment Kit: To be used only with DF-470

Memory upgrade

MDDR2-256: 256 MB; MDDR2-512: 512 MB, MDDR2-1024: 1,024 MB

SD* Card: CF-4 (4 GB) for printing forms, fonts, logos, macro storage

Others

USB Flash Memory: Supports direct printing and scanning of PDF, XPS, TIFF, JPEG files via USB Host interface

Optional Interfaces

Fax System (U): Fax System

IB-50: Gigabit Ethernet Interface

UG-33: ThinPrint support

CB-470 Cabinet: Wooden desk with storage capacity, including castors (wheels)

CB-471 Cabinet: Wooden base for height increase (to be used only with PF-470 or PF-471)

Consumables

TK-475 Toner Kit: Microfine toner black for 15,000 pages A4 in accordance with ISO/IEC 19752

Capacity of starter toner is 3,000 pages in accordance with ISO/IEC 19752

Warranty

KYOCERA MITA UK provides 2-year on-site warranty as standard. KYOCERA guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYO LIFE Up to 5-year on-site warranty extensions available for product and options.



Product depicted includes optional extras.

Kyocera Mita (UK) Ltd, 8 Beacontree Plaza, Gillette Way, Reading, RG2 0BS
Tel: 0118 931 1500, Fax: 0118 931 1108
www.kyoceramita.co.uk, info@kyoceramita.co.uk

* Kyocera does not warrant that any specification mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks and their respective holders are hereby acknowledged. **Based on 60 months' usage

KYOCERA